



Outdoor Fiber Optic Cable



Specification

- * IP-67 water and dust protection
- * Factory terminated for high performance
- * -40°C~85°C operating temperature
- * 445N (100 lbs) cable retention
- * 2.0mm to 7.0mm cable diameters for option
- * Low profile in-line receptacle available
- * No installation tools requires
- * 100 minimum mating cycles

Features

- * Provides superior weather resistance for FTTA and other outdoor applications.
- * Allows flexibility to use factory terminated assemblies or pre-terminated or field installed assemblies
- * Suitable for FTTA and outdoor temperature extremes Ensures functionality in harsh weather environments
- * Can be installs without special tooling
- * Threaded style coupling
- * Provides bend protection for installation and long term use
- * Faster network roll out and customer installations
- * 100% tested assemblies built in a controlled environment
- * Lower cost deployment by utilizing plug and play solutions
- * Custom built solutions with quick turnaround times

Item	Data
Application	Aerial, Direct Buried, Duct
Cable Type	Outdoor Cable
Fiber Type	G657A1/G657A2/G657B3, customized
Termination	One end or both ends
Product Type	Drop Assemblies
Connector A	Huawei Mini SC APC Connector
Connector B	No connector, SC APC or Huawei Mini SC APC Connector
Cable Length	Customized
Operation Temperature	-40 °C to 70 °C (-40 °F to 158 °F)
Insertion Loss	≤0.2dB
Return Loss	≥55dB

Packaging and delivery

Packaging Details

Export Carton Packing

Export Port: Shenzhen, China

Supply Ability

3000 Piece/Pieces per Day