

## Fiber Distribution Box with 10 Ports

## Description

The Fiber distribution box is 10 ports design 1pcs 30/70 Uneven 1:9 optical spliter included. It is used as a termination point for the feeder cable to connect with drop cable in FTTX network system. It integrates fiber splicing, splitting, distribution, storage and cable connection in one soild protection box. This design very easy for setup to connect.

## **Features**

- ♦ Water-proof, dust-proof, anti-aging design,water-proof protection level up to IP68.
- ♦ Integrated with splice cassette and cable management rods.
- ♦ Control the fiber radius of curvature within a reasonable range.
- ♦ Easy to maintain and extend the capacity.
- ♦ The fiber radius of curvature is over 40mm.
- ♦ Be suitable for the fusion splice or mechanical splice.
- ♦ Efficient cable management.
- ♦ Working temperature: -40°C~+60°C
- ♦ Storage temperature: -40°C~+60°C
- ♦ Relative humidity: less than 90% (+40°C)
- ♦ Atmospheric pressure: 70~106kpa



Material	Size	Max Capacity		Mounting Way	Weight	Color
PC/ABS	L*W*H(mm) 210x210x95	SC 10 Ports	Mini PLC 2/1*4 (sc) 1*2/1*8 /1*9	Wall Mounting	1KG	Green/Black

## Detailed product pictures



