

FTTH Drop Cable with Pulling net and Ring



Model Number	SC
Type	Floor Optic Cable
Place of Origin	Guangdong, China
Number of Conductors	1
Fiber Type	G657A, G652D, single mode multi mode
Cable Length	20m 50m 100m or customized
Fiber count	1-12 cores
Application	Indoor /outdoor used
Cable type	FTTH FLAT DROP CABLE
Jacket color	Black white
Outer Jacket	PVC, LSZH, OFNP, PE
Strength member	FRP Strength member
OM Type	9/125UM, 50/125UM, 62.5/125UM, 9/125UM, 50/125UM, 62.5/125UM
Compliance	ISO9001, ROHS

Application:

- ◆ Access Network
- ◆ Telecom/CATV Systems
- ◆ FTTx

FTTH drop cable fiber optic patch cord Performance Parameter			
Name	FTTH drop cable fiber optic patch cord		
Ferrule type	zirconia ceramics ferrule		
IL	≤0.3dB	RL	≥55dB
Fiber core	1,2,4 to 12	Durability	≥1000 times
Jacket	3.1*2.0 or 5.0*2.0mm PVC or LSZH	Wavelength	1310 1550nm
Length	1~1000 meter	Working temperature	-40°C~+80°C