


Outdoor FiberOptic Cable



Specification:

- ◆ IP-67 water and dust protection
- ◆ Factory terminated for high performance
- ◆ -40°C~85°C operating temperature
- ◆ 445N (100 lbs) cable retention
- ◆ 2.0mm to 7.0mm cable diameters for option
- ◆ Low profile in-line receptacle available
- ◆ No installation tools requires
- ◆ 100 minimum mating cycles

Features:

- ◆ Provides superior weather resistance for FTTH and other outdoor applications.
- ◆ Allows flexibility to use factory terminated assemblies or pre-terminated or field installed assemblies
- ◆ Suitable for FTTH and outdoor temperature extremes Ensures functionality in harsh weather environments

- ◆ Can be installs without special tooling
- ◆ Threaded style coupling
- ◆ Provides bend protection for installation and long term use
- ◆ Faster network roll out and customer installations
- ◆ 100% tested assemblies built in a controlled environment
- ◆ Lower cost deployment by utilizing plug and play solutions
- ◆ Custom built solutions with quick turnaround times

Item	Data
Application	Aerial, Direct Buried, Duct
Cable Type	Outdoor Cable
Fiber Type	G657A1/G657A2/G657B3, customized
Termination	One end or both ends
Product Type	Drop Assemblies
Connector A	Huawei Mini SC APC Connector
Connector B	No connector, SCAPC or Huawei Mini SCAPC Connector
Cable Length	Customized
Operation Temperature	-40 °C to 70 °C (-40 °F to 158 °F)
Insertion Loss	≤0.2dB
Return Loss	≥55dB

Packaging and delivery

- ◆ Packaging Details
- ◆ Export Carton Packing
- ◆ Export Port: Shenzhen, China

Supply Ability

- ◆ 3000 Piece/Pieces per Day