

Features:

1. Sliding tray design
2. FTTX FTTH solutions
3. Easy for installation and operation
4. 19" standard structure
5. Available for the installation of FC/SC/ST/LC adapters

Application:

1. Data Center LAN/SAN
2. Telecommunications subscriber loop
3. Fiber to the home (FTTH)
4. High density cable wiring system
5. High integrated equipment and devices
6. Made of cold-rolling steel, static spreading-plastic, small dimension and exquisite and easy for operation

Advantages:

- The box are Rack Mounted, which is convenient to install and dismantle;
- The splice tray could be piled one upon another, flexible to turn;
- The curve radius of the coiled spear fibers should be guaranteed to be over 37.5mm in the splice tray;
- The box is of unique structure, reasonable layout, and has adequate room for operation
- Adjustable clamp seal ring and reinforce configuration, which could adjust different sizes of cables flexibly to make sure the cables are clamp tightly;
- The indoor type is of excellent seal performance, which could prevent water from entering effectively;

Specifications:

Type	12MS-6	12MS-12	12ML-6	24ML-6
Fiber Type	SM, MM, OM3, OM4			
Fiber Count	12	12	12	24
Number of Adapters per Panel	6	12	6	6
Adapter Type Front	SC Duplex	SC Simplex	LC Duplex	LC Quad
Adapter Color Front	Blue, Beige, Aqua, Purple			
Adapter Type Back	MPO/MTP			
Adapter Color Back	Black			



